Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

- (Currently Amended) A wind power installation <u>positioned on a ground</u> and having a machine housing fitted to a pylon, the machine housing including a rotor and a generator connected thereto, the wind power installation comprising:
- a flight lighting arrangement which produces a light that is visible from a distance; and includes
- a cover that prevents-configured to prevent a substantial amount of the light from the flight lighting arrangement from being seen from the ground in a region of 0 m to approximately 2000 m around the wind power installation.
- (Currently Amended) The wind power installation according to claim 1
 wherein the region comprises an area-of-about 0-to-1000-m around the wind-power installation to
 a height of about 3 to 10 m.
- (Previously Presented) The wind power installation according to claim 1 wherein the cover comprises a plate located beneath and/or laterally of the flight lighting arrangement.
- (Previously Presented) The wind power installation according to claim 1
 wherein the cover has a parabolic configuration, and the flight lighting arrangement is disposed
 within the cover.
- (Currently Amended) The wind power installation according to claim 1
 wherein the cover is of such a configuration that to prevent the light from being seen from the

ground in the region comprises an area of about 0 to 2000 maround the wind power installation independently of an azimuth-adjustment of the machine housing angle of the wind power installation.

- (Previously Presented) The wind power installation according to claim 1
 wherein the cover comprises a plate that extends laterally outward from the flight lighting
 arrangement.
- (Previously Presented) The wind power installation according to claim 4
 wherein the cover permits the light of the flight lighting arrangement to be visible at an angle of
 -10 to 90°, with respect to the horizontal.

(Cancelled)

- 9. (Currently Amended) A wind power installation comprising:
- a flight lighting arrangement that produces a light that alerts air traffic as to an approximate location of the wind power installation; and
- a cover positioned beneath the flight lighting arrangement that substantially blocks an amount of the light of the flight lighting arrangement from a region below the cover and in the area of 0 m to approximately 2000 m around the wind power installation.
- (Previously Presented) The wind power installation of claim 9 wherein the light is a flashing signaling light.
- (Previously Presented) The wind power installation of claim 10 wherein the flashing signaling light flashes from time to time.
- (Previously Presented) The wind power installation of claim 10 wherein the flashing signaling light flashes constantly.

- (Previously Presented) The wind power installation of claim 9 wherein the cover comprises a large circular disc.
- (Previously Presented) The wind power installation of claim 9 wherein the cover is configured to have a parabolic shape.
- (Previously Presented) The wind power installation of claim 9 wherein the cover is configured to have a box-shape.
- (Previously Presented) The wind power installation of claim 9 wherein the cover includes a mirrored surface.
- 17. (Previously Presented) The wind power installation of claim 9 wherein a size and shape of the cover determines at least in part the amount of light that is blocked from the region below and around the wind power installation.
- 18. (Previously Presented) The wind power installation of claim 9 wherein the region below the cover and around the wind power installation is defined by a volume corresponding to a cone frustum.
- 19. (New) A wind power installation having a machine housing fitted to a pylon, the machine housing including a rotor and a generator connected thereto, the wind power installation comprising:
- a flight lighting arrangement which produces a light that is visible from a distance; and
- a cover configured to prevent a substantial amount of the light from the flight lighting arrangement from being seen from the ground in a region in the area of $0\,\mathrm{m}$ to approximately 700 m around the wind power installation.

- 20. (New) A wind power installation having a machine housing fitted to a pylon, the machine housing including a rotor and a generator connected thereto, the wind power installation comprising:
- a flight lighting arrangement which produces a light that is visible from a distance; and

a cover positioned with respect to the flight lighting arrangement to permit the light from the flight lighting arrangement be visible only at an angle of approximately -10 to 90° measured from the flight lighting arrangement with respect to the horizontal.

21. (New) A wind power installation comprising:

- a flight lighting arrangement that produces a light that alerts air traffic as to an approximate location of the wind power installation; and
- a cover positioned beneath the flight lighting arrangement that substantially blocks the light of the flight lighting arrangement from a region below the cover and more than 0 m to approximately 700 m around the wind power installation.